

Flow Control

Mid Size



Product Variations

DXM2D015A.11421

Part No:	DXM2D015A.11421
Nominal Dimension [DN]:	15
Pressure Rating [PN]:	16
Max Flow Rate:	3,800 l/h 0.472 l/s
Min Flow Rate:	380 l/h 0.142 l/s
Kvs:	3.8
Weight [kg]:	4,7
Min Temperature [°C]:	15
Max Temperature [°C]:	80
Connection Size:	1/2"
Connection Type:	flat connections, according to ISO228/1, incl. connection parts with cylindrical inside thread acc. ISO7/1, union nuts and gaskets

Flow Control

Mid Size

DXM2D020A.11421

Part No:	DXM2D020A.11421
Nominal Dimension [DN]:	20
Pressure Rating [PN]:	16
Max Flow Rate:	5,700 l/h 0.708 l/s
Min Flow Rate:	570 l/h 0.212 l/s
Kvs:	5.7
Weight [kg]:	6,2
Min Temperature [°C]:	15
Max Temperature [°C]:	80
Connection Size:	3/4"
Connection Type:	flat connections, according to ISO228/1, incl. connection parts with cylindrical inside thread acc. ISO7/1, union nuts and gaskets

Flow Control

Mid Size

DXM2D025A.11421

Part No:	DXM2D025A.11421
Nominal Dimension [DN]:	25
Pressure Rating [PN]:	16
Max Flow Rate:	8,000 l/h 0.993 l/s
Min Flow Rate:	800 l/h 0.298 l/s
Kvs:	8
Weight [kg]:	6,5
Min Temperature [°C]:	15
Max Temperature [°C]:	80
Connection Size:	1"
Connection Type:	flat connections, according to ISO228/1, incl. connection parts with cylindrical inside thread acc. ISO7/1, union nuts and gaskets

Flow Control

Mid Size

DXM2D032A.11421

Part No:	DXM2D032A.11421
Nominal Dimension [DN]:	32
Pressure Rating [PN]:	16
Max Flow Rate:	10,300 l/h 1.279 l/s
Min Flow Rate:	1,030 l/h 0.383 l/s
Kvs:	10.3
Weight [kg]:	8,2
Min Temperature [°C]:	15
Max Temperature [°C]:	80
Connection Size:	1 1/4"
Connection Type:	flat connections, according to ISO228/1, incl. connection parts with cylindrical inside thread acc. ISO7/1, union nuts and gaskets

Flow Control

Mid Size

DXM2D040A.11421

Part No:	DXM2D040A.11421
Nominal Dimension [DN]:	40
Pressure Rating [PN]:	16
Max Flow Rate:	21,200 l/h 2.633 l/s
Min Flow Rate:	2,120 l/h 0.790 l/s
Kvs:	21.2
Weight [kg]:	11,0
Min Temperature [°C]:	15
Max Temperature [°C]:	80
Connection Size:	1 1/2"
Connection Type:	flat connections, according to ISO228/1, incl. connection parts with cylindrical inside thread acc. ISO7/1, union nuts and gaskets

Flow Control

Mid Size

DXM2D050A.11421

Part No:	DXM2D050A.11421
Nominal Dimension [DN]:	50
Pressure Rating [PN]:	16
Max Flow Rate:	28,300 l/h 3.515 l/s
Min Flow Rate:	2,830 l/h 1.055 l/s
Kvs:	28.3
Weight [kg]:	12,6
Min Temperature [°C]:	15
Max Temperature [°C]:	80
Connection Size:	2"
Connection Type:	flat connections, according to ISO228/1, incl. connection parts with cylindrical inside thread acc. ISO7/1, union nuts and gaskets