

Pre-Settable

1-1/2" – 2" Cast Iron



Pre-Settable

1-1/2" – 2" Cast Iron

Product Variations

PE83SLN.12

Part No:	PE83SLN.12
Short Description:	PICV, L Flow, DN40 (1 1/2")
Nominal Dimension [DN]:	40
Pressure Rating [PN]:	16
Max Flow Rate:	6000 l/h 1.67 l/s
Min Flow Rate:	1800 l/h 0.50 l/s
Weight [kg]:	15.3
Min Temperature [°C]:	-10
Max Temperature [°C]:	120
Connection Size:	1 1/2"
Connection Type:	Rc 1 1/2" union F EN 10226-1

Pre-Settable

1-1/2" – 2" Cast Iron

PE83SHN.12

Part No:	PE83SHN.12
Short Description:	PICV, H Flow, DN40 (1 1/2")
Nominal Dimension [DN]:	40
Pressure Rating [PN]:	16
Max Flow Rate:	9000 l/h 2.5 l/s
Min Flow Rate:	2700 l/h 0.75 l/s
Weight [kg]:	15.5
Min Temperature [°C]:	-10
Max Temperature [°C]:	120
Connection Size:	1 1/2"
Connection Type:	Rc 1 1/2" union F EN 10226-1

Pre-Settable

1-1/2" – 2" Cast Iron

PE83SLN.16

Part No:	PE83SLN.16
Short Description:	PICV, L Flow, DN40 (with 2" unions)
Nominal Dimension [DN]:	40
Pressure Rating [PN]:	16
Max Flow Rate:	11000 l/h 3.06 l/s
Min Flow Rate:	3300 l/h 0.9 l/s
Weight [kg]:	15.3
Min Temperature [°C]:	-10
Max Temperature [°C]:	120
Connection Size:	2"
Connection Type:	Rc 2" union F EN 10226-1

Pre-Settable

1-1/2" – 2" Cast Iron

PE83SHN.16

Part No:	PE83SHN.16
Short Description:	PICV, High Flow, DN50 (2")
Nominal Dimension [DN]:	50
Pressure Rating [PN]:	16
Max Flow Rate:	18000 l/h 5.00 l/s
Min Flow Rate:	5400 l/h 1.5 l/s
Weight [kg]:	15.5
Min Temperature [°C]:	-10
Max Temperature [°C]:	120
Connection Size:	2"
Connection Type:	Rc 2" union F EN 10226-1