

Rotary

65mm-150 Cast Iron Flanged

Rotary

65mm-150 Cast Iron Flanged

Product Variations

PE94FL.80

Part No:	PE94FL.80
Short Description:	PICV, DN80 (2 1/2")
Pressure Rating [PN]:	16
Max Flow Rate:	30000 l/h 8.33 l/s
Min Flow Rate:	3000 l/h 2.499 l/s
Weight [kg]:	48
Min Temperature [°C]:	-10
Max Temperature [°C]:	120
Connection Size:	2 1/2"
Connection Type:	Flanged 2 1/2" EN 1092-2 EN 558 (face to face)

Rotary

65mm-150 Cast Iron Flanged

PE94FL.100

Part No:	PE94FL.100
Short Description:	PICV, DN100 (3")
Pressure Rating [PN]:	16
Max Flow Rate:	40000 l/h 11.11 l/s
Min Flow Rate:	4000 l/h 3.333 l/s
Weight [kg]:	60
Min Temperature [°C]:	-10
Max Temperature [°C]:	120
Connection Size:	3"
Connection Type:	Flanged 3" EN 1092-2 EN 558 (face to face)

Rotary

65mm-150 Cast Iron Flanged

PE94FL.125

Part No:	PE94FL.125
Short Description:	PICV, DN125 (4")
Pressure Rating [PN]:	16
Max Flow Rate:	55000 l/h 15.28 l/s
Min Flow Rate:	5500 l/h 4.584 l/s
Weight [kg]:	102
Min Temperature [°C]:	-10
Max Temperature [°C]:	120
Connection Size:	4"
Connection Type:	Flanged 4" EN 1092-2 EN 558 (face to face)

Rotary

65mm-150 Cast Iron Flanged

PE94FH.150

Part No:	PE94FH.150
Short Description:	PICV, DN150 (5")
Pressure Rating [PN]:	16
Max Flow Rate:	80000 l/h 22.22 l/s
Min Flow Rate:	8000 l/h 6.666 l/s
Weight [kg]:	126
Min Temperature [°C]:	-10
Max Temperature [°C]:	120
Connection Size:	5"
Connection Type:	Flanged 5" EN 1092-2 EN 558 (face to face)